



Reflection






## SILK COLLECTION

Elegance, Functionality & Freedom of design

PCS Porcelain mosaics are a cultivation of a feeling, creation of expectation & excitement, a promise of quality & service – an emotional responce to architectural needs with different looks and colours.

PCS gives you the flexibility to select, mix and merge – items, techniques, sizes, looks and colours. Such combinations create infinite and unique design possibilities to suit your taste and ambience.

Through PCS range, designer have freedom to explore 1000+ options with 7 sizes, 6 looks and 200+ colours.













				DIMENSIO	N & WEIG	HT				
Particulars		Aligned							Classic / Modula	
		2.5 x 2.5 cm	2.5 x 5 cm	2.5 x 7.5 cm*	5 x 5 cm	5 x 10 cm	7.5 x 7.5 cm*	10 x 10 cm	Design dependent	
Mosaic	Nominal Size	2.5 x 2.5 cm	2.5 x 5 cm	2.5 x 7.5 cm	5.07 x 5.07 cm	5.07 x 10.07 cm	7.6 x 7.6 cm	10.1 x 10.1 cm	Design dependent	
	Actual Size	2.34 x 2.34 cm	2.34 x 4.84 cm	2.34 x 7.34 cm	4.84 x 4.84 cm	4.84 x 9.84 cm	7.34 x 7.34 cm	9.84 x 9.84 cm	Design dependent	
	Thickness	~ 8 mm						Aug		
Sheet	Mosaic Pcs.	12 x 12 = 144 Pcs.	12 x 6 = 72 Pcs .	12 x 4 = 48 Pcs.	6 x 6 = 36 Pcs.	6 x 3 = 18 Pcs.	4 x 4 = 16 Pcs.	3 x 3 = 9 Pcs.	Design dependent	
	Nominal Size	30 x 30 cm	30 x 30 cm			30.42 x 30.21 cm		30.42 x 30.42 cm	Design dependent	
	Actual Size	29.84 x 29.84 cm	29.84 x 29.84 cm		30.19 x 30.19 cm	30.19 x 29.98 cm	30.15 x 30.15 cm	30.12 x 30.12 cm	Design dependent	
	Joint Gap	~ 1.6 mm	~ 1.6 mm	-1.6 mm		~ 2.30 mm	~ 2.65 mm	~ 3.0 mm	~ 1.6 mm	
	Coverage	0.090m <sup>2</sup> / 0.969H <sup>2</sup>	0.090m <sup>2</sup> / 0.969H <sup>2</sup>	0.090m <sup>2</sup> / 0.969ft <sup>2</sup>	0.093m <sup>2</sup> / 0.996ft <sup>2</sup>	0.092m <sup>2</sup> / 0.989H <sup>3</sup>	0.093m <sup>2</sup> / 0.996H <sup>3</sup>	0.093m² / 0.996ft²	Design dependent	
	Weight	~ 1.500 kgs								
Sq.Mtr.	No. of sheets	~11								
	Weight	~ 16.500 kgs								

TECHNICAL CHARACTERISTICS & TEST DATA								
4	WATER ABSORPTION	ISO 10545-3	≤ 0.5%					
<u>\( \)</u>	BREAKING STRENGTH	ISO 10545-4	Passes					
$\boxed{\begin{array}{c} \downarrow \\ \uparrow  \uparrow \end{array}}$	MODULUS OF RUPTURE	ISO 10545-4	Passes					
	RESISTANCE TO GLAZE ABRASION	ISO 10545-7	Resistant					
类	RESISTANCE TO THERMAL SHOCK	ISO 10545-9	Resistant					
	RESISTANCE TO GLAZE CRACKING	ISO 10545-11	Resistant					
※	RESISTANCE TO FROST	ISO 10545-12	Resistant					
	RESISTANCE TO CHEMICAL ATTACK	ISO 10545-13	Resistant					
\$F	RESISTANCE TO STAIN	ISO 10545-14	Resistant					
	LIGHT AND COLOUR FASTNESS	DIN 51094 / \$\$301	Passes					
	LIGHT AND COLOUR FASTNESS	DIN 51094 / \$\$301						

"Available in "Aqua" collection

Mesaic colours shown here are purely indicative, tonal variation is an inherent characteristics of high temperature fired product.














Strenght

PCS Porcelain mosaic being small format and having 8mm thickness, it has high modulus of rupture (MOR) value, wich makes the product stronger and sustainable in floor areas.



Customization

Being an architect or interior designer, you would like to customise your imagination from project to project. PCS porcelain mosaic can facilitate you in this concern as PCS is having equiped design studio to convert your design imagination into reality.



Safety

In Additional to aesthetic appeal & funcional benefits, one of the important aspects of interior designing is safety of people linving in. PCS ensures the deepest concern of safety as mosaics with gaps give a better grip underfoot, especially in wet areas like bathroom, kitchen, swimming pools etc.



Compatibility

Due to thickness of 8mm, PCS porcelain mosaics are compatible with all ceramic tiles.


















■ 2.5 x 2.5 cm | 5 x 5 cm | 10 x 10 cm ■ 2.5 x 5 cm | 5 x 10 cm





















CTG SRL Via Quattro Passi 2A 41043 Formigine (MO), Italy P.Iva 02706420367